

EBCO INTERNAL METER KITS FOR INLINE METERS

10 Bar pressure rating



EBCO water meter kits make it easy to fit inline water meters internally in a property. Different kits are available to suit various pipework and meter sizes for all applications. The standard kit comes with a straight meter tail on one side and on the other side a straight meter tail with an integrated ball valve and drain off point. Also available are plain straight meter tail kits DN15-DN40 and 90 degree meter tails DN15 and DN20.

Feature	Specification
Shut Off Device	1/4 Turn
Meter Connection	For inline meter

PRODUCT CODE	PIPE DIA. INLET MM	INLET CONNECTION	PIPE DIA. OUTLET MM	OUTLET CONNECTION	METER NOMINAL SIZE	METER CONNECTION
MKCF1515	15	Compression	15	Compression	DN15	Rp 3/4" BSP
MKCF2222	22	Compression	22	Compression	DN20	Rp 1" BSP
MKPF1515	15	Brass tail for compression / press	15	Brass tail for compression / press	DN15	Rp 3/4" BSP
MKPF2222	22	Brass tail for compression / press	22	Brass tail for compression / press	DN20	Rp 1" BSP
MKPFS1515	15	Press fit socket	15	Press Fit Socket	DN15	Rp 3/4" BSP
MKPFS2222	22	Press fit socket	22	Press Fit Socket	DN20	Rp 1" BSP

The technical data and performance may be modified without prior notice depending on the technical advances.

EBCO INTERNAL METER KITS FOR INLINE METERS

General application

The EBCO Internal Meter Kit for inline meters allows the fitting of an inline meter inside a property.

The EBCO Internal Meter Kit also includes a rotatable drain off plug which allows for draining down of the property's water pipes.

Inlets and outlets are either 15mm or 22mm compression, brass tails for press fittings or press fit sockets.

Safety

As with all industrial products it is important to take adequate safety precautions such as the use of adequate protective clothing like gloves, overalls, eye protection and safety footwear during installation, use and maintenance with this product.



Technical data

Pressures	Working	Test
Water:	10 bar	15 bar

Temperature: Up to 23°C

Temperature increases may affect the installed life of the product. For further information relating to operating temperatures/pressure please contact Atplas.

Materials

Body: CW602N DZR Brass

O-rings and washers: EPDM

Seat: PTFE

Please note that meters are not supplied with the EBCO Internal Meter Kit.

How to order

The EBCO Internal Meter Kit for internal meters can be supplied:

- with 15mm or 22mm inlets or outlets
- with compression or press fit sockets
- with meter connections Rp 3/4" BSP or Rp 1" BSP
- with compression ends, tails for press fit, or press fit socket, 15mm or 22mm